



## Plug-lid-cans and Plug-lid-pails for chemical products

Diameter	Height	Remarks
99	65 - 250 mm	Cylindrical, ball-ears and handle on request.
117	75 - 250 mm	Cylindrical.
130/125	85 - 300 mm	Cylindrical, stackable, bottom necking, ball-ears and handle on request.
140	90 - 300 mm	Cylindrical, ball-ears and handle on request, handle mounted.
160	104 - 300 mm	Cylindrical, ball-ears and handle on request, handle mounted.
160/153	104 - 300 mm	Cylindrical, stackable, bottom necking, ball-ears and handle on request, <b>available BAM-certified for dangerous goods: UN /1A2/Y/100/year/D/BAM, JKD.</b>
163	100 - 300 mm	Cylindrical.
190	150 - 300 mm	Cylindrical, ball-ears and handle on request.
190/180	150 - 300 mm	Conical, stackable, ball-ears and handle on request.
230/217	165 - 348 mm	Conical, stackable, special beading for hot-filling on request - vacuum-pails and vacuum-ends; bottom end with triple-seam. <b>available BAM-certified for dangerous goods: UN /1A2/Y/100/year/D/BAM, JKD.</b>
235/224	165 - 348 mm	Conical, stackable.

- Special sizes on request
- Side seam WIMA welded, inside powder coated, outside protected with varnish.
- Solvent resistant compound in the bottom ends - bottom 217 mm with triple-seam.
- Special protective coating inside depending on the product.
- Lid fixation optional by clamping ring, safety-ring (-strip) or ball-ears with integrated overlapping clamps.
- Lids on request with PVC-compound in the end-flange.
- Ball-ears welded, inside welding points covered by 2-component-varnish.
- Conical types stackable to prevent freight- and storing costs.
- 100 % fully automatic piece by piece leak test in all sizes.

